



Monarch Oil (Kitchener) Limited

P.O. BOX 653 808 VICTORIA ST. NORTH, KITCHENER, ONT. N2G 4B6 PHONE (519) 743-8241 TOLL FREE 1-800-268-OILS
 FAX (519) 743-9802 EMAIL: service@monarchoil.com INTERNET www.monarchoil.com

PRODUCT NAME: ANCHLOR 12 SODIUM

AS140

SECTION 01: PRODUCT INFORMATION AND COMPANY INFORMATION

MANUFACTURER: Anchem Sales
PREPARED BY: Production Department
VERSION DATE: 23-Jan-12
TELEPHONE NO.: (519) 451-1614
EMERGENCY PHONE NO.: (613) 996-6666
CHEMICAL FAMILY: Hydrochlorous Acid **CHEMICAL FORMUL:** Na-O-Cl
MOLECULAR WEIGHT: Not Applicable **MATERIAL USE:** Please Refer to technical literature
SYNONYMS: Sodium Hypochlorite, Sodium Hypochlorite 12%, Bleach

SECTION 02: COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients	Conc. Approx. %	C.A.S. #	LD/50 (RTE/SPEC)	LC/50 (RTE/SPEC)	TLV
Sodium Hypochlorite	7-13	7681-52-9	5800 mg/kg (Mouse/Oral)	N.Av.	N.Av.
Water	Balance	7732-18-5	N.Av.	N.Av.	N.Av.

SECTION 03: HAZARD IDENTIFICATION

ROUTE OF ENTRY

Eyes: Extremely hazardous in case of eye contact (irritant).
Skin: Very hazardous. (corrosive, irritant). Skin contact may produce burns.
Inhalation: Hazardous. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Severe over-exposure can result in death.
Ingestion: Very hazardous.

SECTION 04: FIRSTAID

Skin Contact: If the chemical gets on the clothed portion of the body, remove the contaminated clothes as quickly as possible, protecting your own hands and body. Place the victim under a deluge shower. If the chemical touches the victim's exposed skin, such as the hands: Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. Be particularly careful to clean folds, crevices, creases and groin. COLD water may be used. If irritation persists, seek medical attention. Wash contaminated clothing before reusing.

Eye Contact: Check for and remove any contact lenses. IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. COLD water may be used. DO NOT use an eye ointment. Seek medical attention.

Inhalation, Acute: Remove person to fresh air. If not breathing give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Ingestion: DO NOT induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.

Notes to physician: N.Av.

SECTION 05: FIRE EXPLOSION HAZARD AND FIRE FIGHTING MEASURES

FLAMMABLE? No
IF YES, UNDER WHICH CONDITIONS Not applicable.

FLASH POINT (TCC) (C):	N. App.	
FLAMMABLE LIMITS:	LEL(% BY VOL.): N. App	UEL(% BY VOL.): N. App.
AUTO IGNITION TEMPERATURE (C)	N. App.	
EXTINGUISHING MEDIA	N. App.	
SPECIAL PROCEDURES:	N. App.	
HAZARDOUS COMBUSTION PRODUCTS:	Not Available	
UNUSUAL FIRE AND EXPLOSION HAZARDS	Not Available	
SENSITIVITY TO STATIC DISCHARGE	N. App.	
SENSITIVITY TO MECHANICAL IMPACT:	N. App.	

SECTION 06: ACCIDENTAL RELEASE MEASURES

Leak and Spill Procedure: Small Spill: Dilute with water and mop up, or absorb with an inert DRY material and place in an appropriate waste disposal container. If necessary: Neutralized the residue with a dilute solution of sodium sulphite or sodium thiosulphate.

Large Spill: Corrosive Liquid! Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Use water spray curtain to divert vapor drift. Use water spray to reduce vapors. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal. Neutralize the residue with a dilute solution of sodium sulphate or hydrogen peroxide.

SECTION 07: HANDLING AND STORAGE**Handling Procedures and Storage Requirements**

Keep locked up. Keep container dry. Keep away from heat. Keep away from sources of ignition. Keep away from direct sunlight or strong incandescent light. DO NOT ingest. Do not breathe gas, fumes, vapor or spray. Never add water to this product. Avoid shock and friction. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Keep away from incompatibles such as oxidizing agents, acids.

Corrosive materials should be stored in a separate safety storage cabinet or room.

SECTION 08: PERSONAL PROTECTIVE EQUIPMENT / EXPOSURE CONTROL

GLOVES/TYPE:	Impervious chemical resistant gloves.
RESPIRATOR/TYPE:	A NIOSH/MSHA respirator with organic vapor cartridge.
EYE/TYPE:	Safety glasses.
OTHER/TYPE:	Rubber boots.
ENGINEERING CONTROL	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective TLV. Ensure that eyewash stations and safety showers are proximal to the work-station location.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE/APPEARANCE:	Liquid - Green To Yellow		
ODOUR:	Chlorine (strong)	ODOUR THRESHOLD:	N. Av.
VAPOUR PRESSURE (mm Hg @ 20C):	17.5	VAPOUR DENSITY (Air=1):	1
EVAPORATION RATE (Ether = 1):	N. Av.	SPECIFIC GRAVITY:	1.16
BOILING POINT (C):	Decomp. @ 40	FREEZING POINT (C)	-25
Ph (% SOLUTION):	12.25	% VOLATILE (WT):	N. Av.
SOLUBILITY IN WATER (% W/W)	Completely		

SECTION 10: STABILITY AND REACTIVITY

CHEMICALLY STABLE? No

IF NO, UNDER WHICH CONDITIONS? Under normal conditions: Unstable above 40 C, sunlight, contact with metals.
Under Fire conditions: Unstable.

INCOMPATIBILITY WITH OTHER SUBSTANCES Yes

IF YES, WITH WHICH ONES: Reactive with strong acids, reducing materials, oxidizable materials, urea, nickel, copper, tin, manganese, ammonia, iron.

SPECIAL REACTIVITY AND UNDER WHAT CONDITIONS Hazardous decomposition products: Chlorine (contact with acids)

HAZARDOUS DECOMPOSITION PRODUCTS: N. Av.

SECTION 11: TOXICOLOGICAL INFORMATION

EXPOSURE LIMIT OF MATERIAL 0.5 ppm as for chlorine
LC 50 OF MATERIAL, SPECIES AND ROUTE See Sec. 2
LD 50 OF MATERIAL, SPECIES AND ROUTE See Sec. 2
CARCINOGENICITY OF MATERIAL N. Av.
REPRODUCTIVE EFFECTS: N. Av.
IRRITANCY OF MATERIAL N. Av.
SENSITIZING CAPABILITY OF MATERIAL N. Av.
SYNERGISTIC MATERIALS N. Av.

SECTION 12: ECOLOGICAL INFORMATION

AQUATIC TOXICITY N. Av.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Recycle to process, if possible. Consult your local or regional authorities.

SECTION 14: TRANSPORT INFORMATION

TDG CLASSIFICATION Class 8, Hypochlorite Solutions
UN NUMBER: 1791
PACKING GROUP: III
Special Provisions for Transport

SECTION 15: REGULATORY INFORMATION

WHMIS CLASSIFICATION D.2B E

SECTION 16: OTHER INFORMATION

ABBREVIATIONS USED: N.Av. = Not Available
N.App. / N.Ap. = Not Applicable

DISCLAIMER: Although the information herein is to the best of our knowledge accurate, no guarantee expressed or implied, is made regarding the information or the performance of any product. We assume no liability for incidental or direct damages of any kind, no matter what, including negligence.

SOURCES: Supplier MSDS

For updated copies of an MSDS, please contact Anchem Sales at the address/phone number on Page 1 or fax the MSDS Co-ordinator at (519) 451-4593.

LAST PAGE

Form 074 Issued Mar/06